Sheerspeed Shelters Ltd.

Unit 3, Reme Drive, Honiton, Devon, EX14 1SE

Tel: +44 (0) 1404 46006

Email: sales@sheerspeed.com Website: www.sheerspeed.com

### **Standard Specifications:**

- 500gms Heavy-duty PVC reinforced FR material
- PVC & LACQUER coated on both sides of material Easy clean after dust containment.
- 100% waterproof RF welding process fusing all material joints.
- Wet storage properties.
- Translucent PVC roof NATURAL light ingress Reduced operator fatigue.
- RF Welds create enhanced seal to prevent dust escaping.
- Robust Die cast central joints Protective cover prevents operator pinching–Unique Sheerspeed design.
- Rubber protected feet good grip and non-slip with extended product life protection.
- No Loose components Integral Frame & Cover.
- Zip front door. (3 zips on models 2.7m and above)
- Tent joining linking two tents together for larger covered areas.
- Rear 2 zip door access Access when tents are against walls / vehicles or linked together.
- Lifting handles External tent manoeuvring.
- Front support poles (2off) increased tent stability (larger tents 2.5m+) – Where tents are on location for a number of days and/or more extreme weather conditions.
- Metal weight pouches Internal & integrated NEW feature - (Hard surfaces & Soft ground)
- 4off extra external guy line points Top 4 corners.
- Non-conductive Fibreglass framework.
- Manufacturer guarantee.
- 7off Guy straps & Tent pegs Adjustable.
- All spares available and tent repairs.
- Heavy Duty Carry bag

#### **Additional options:**

- Wheeled Carry bag
- Additional lower section colours.
- PU Coated Nylon material.
- Vents hooded or mesh.
- Additional front & rear Zips.
- Windows.
- Logos & Branding.
- Tent repair Kits.

# Manufactured from European sourced materials.

# <u>Speed Tent – Square -</u>

## **Dust Enclosure Tents 2025** – Iss.01

TYPE	SIZE (I)x(w)x(h)	(Kg)	Fold size
	0.22 (//.(/(/	(1.6)	l x w x h (m)
			, ,
100 5SP NS	1.0x1.0x1.8m	10	0.95x0.2x0.2
	(3.0x3.0x6ft)		
125 5SP NS	1.25x1.25x2.0m	14	1.40x0.25x0.25
125 55P NS	(4x4x7ft)	14	1.40x0.25x0.25
	` ,		
150 5SP NS	1.5x1.5x2.0m	16	1.40x0.25x0.25
	(5x5x7ft)		
180 5SP NS	1.8 x 1.8 x 2.0 m	17	1.45x0.25x0.25
	(6x6x7ft)		
200 5SP NS	2.0 x 2.0 x 2.0 m	18	1.55x0.30x0.30
	(6.5x6.5x7ft)		
210 5SP NS	2.1 x 2.1 x 2.0 m	19	1.6x0.30x0.30
	(7x7x7ft)		
250 5SP NS	2.5 x 2.5 x 2.0 m	24	1.70x0.30x0.30
	(8x8x7ft)		
270 5SP NS	2.7 x 2.7 x 2.0 m	26	1.82x0.35x0.35
270 33F N3	(9x9x7ft)	20	1.82x0.33x0.33
	,		
300 5SP NS	3.0 x 3.0 x 2.2 m	28	1.95x0.35x0.35
	(10x10x7ft)		
360 5SP NS	3.6 x 3.6 x 2.4 m	39	2.25x0.35x0.35
	(12x12x8ft)		
400 5SP NS	4.0 x 4.0 x 2.4 m	46	2.5x0.35x0.35
	(13x13x8ft)		
CB11	H D PVC Carry Bag	Up to 7ft	
CBII	I DrvC Cally Bag	οριο / π	
CB11ext	H D PVC Carry Bag	8 to 10ft	
CB12	H D PVC Carry Bag	12 to 13ft	
	l .		l .

# ALL sizes available! – Just let us know your desired dimensions



Sheerspeed's Unique Translucent roof design allowing maximum NATURAL light into tent working area.





UNBEATABLE Fold size (1.95x0.35x0.35m)

Wheeled Carry Bag - Compact, lightweight, and equipped with sturdy heavy-duty wheels.

Protecting tents and equipment during transportation. 5off carry handles and tent compacting straps.

## **Standard Features:**





Rear door - std. 3 zip front door - std. 3m +





Integrated tent pouches
Metal disc weight

Tent joining – std. 2off 3m x 3m Total (6mx 3m)

Credit card purchase facilities available. (2.7% transaction charge Business cards)





